EVOKO LISO


TECHNICAL SPECIFICATION

TECHNICAL INFO

- Display
- . 8 inch capacitive touch with antifingerprint treatment
- Connectivity
 - Wi-Fi
 - o 802.11 a/b/g/n
 - Ethernet
 - o RJ-45, 10/100/1000 Mbit
 - O PoE & PoE +
 - o IEEE 802.3af
 - RFID 13.56 MHz
 - oreader
 - ISO/IEC 14443A/B

 - Supports MIFARE 4K/1K card (does not support ISO/IEC 15693 or MIFARE Ultralight C)
- Power
 - Power over Ethernet (PoE), or
 - 12V AC/DC power adapter (accessory)
- Sensors
 - Proximity sensor
 - · Ambient light sensor
- Mounting
 - Mounting options for both standard and glass walls
 - 5-way cable exit option for easy and neat installation
- Other
 - 3-way indirect light aura to make room
 - status visible already from a distance Open API for third party integration
 - Communication via real-time two-way connection
 - · Remote management with multi-site support
 - · Real-time monitoring & statistics

 - · Recommended Specifications: Dual Core CPU-4GB-30GB



COMPATIBLE PLATFORMS

- Microsoft Office 365
- · Microsoft Exchange 2016
- Microsoft Exchange 2013
- · Google G Suite
- IBM/Lotus Domino Smartcloud
- IBM/Lotus Domino 8.5.3 9.x
- Evoko Booking (stand-alone version)

SIZE AND WEIGHT

- Size: 200 x 200 x 25 mm (7.9 x 7.9 x 1.0 inch)
- Weight: 1.3 kg (2.9 lbs)

USER INTERFACE LANGUAGES

- Arabic
- Catalan
- · Chinese, Simplified
- Chinese. Traditional
- Czech
- Danish
- Dutch
- English Estonian
- Finnish
- French
- Galician German
- Italian
- Icelandic
- Japanese
- Korean
- Latvian
- Lithuanian
- Norwegian
- Polish
- Portuguese
- Russian
- Spanish
- Swedish
- Thai

PRICING MODEL & BOX CONTENTS

Our pricing model is based on the same simplicity as our products; it is a one-time cost per unit and that is it. There are no licensing costs or subscription fees and all required hardware, software, support and warranty are included. The one-time cost includes:

- · Evoko Liso unit (hardware with Liso application)
- · Mounting kits for both standard and glass walls
- Evoko Home application (used for configuration, synchronization and administration)
- Future software upgrades for the Evoko Liso unit and Evoko Home
- Power Supply (if needed, typically installed with PoE)
- 2-year warranty (up to 3 more years can be purchased separately)
- Product support via phone/email/ web-tickets for as long as the Liso units are used

ARTICLE NUMBER

ERM2001

